

Cloudera ODBC Driver for Impala Version 2.5.31



Important Notice

© 2010-2016 Cloudera, Inc. All rights reserved.

Cloudera, the Cloudera logo, Cloudera Impala, Impala, and any other product or service names or slogans contained in this document, except as otherwise disclaimed, are trademarks of Cloudera and its suppliers or licensors, and may not be copied, imitated or used, in whole or in part, without the prior written permission of Cloudera or the applicable trademark holder.

Hadoop and the Hadoop elephant logo are trademarks of the Apache Software Foundation. All other trademarks, registered trademarks, product names and company names or logos mentioned in this document are the property of their respective owners. Reference to any products, services, processes or other information, by trade name, trademark, manufacturer, supplier or otherwise does not constitute or imply endorsement, sponsorship or recommendation thereof by us.

Complying with all applicable copyright laws is the responsibility of the user. Without limiting the rights under copyright, no part of this document may be reproduced, stored in or introduced into a retrieval system, or transmitted in any form or by any means (electronic, mechanical, photocopying, recording, or otherwise), or for any purpose, without the express written permission of Cloudera.

Cloudera may have patents, patent applications, trademarks, copyrights, or other intellectual property rights covering subject matter in this document. Except as expressly provided in any written license agreement from Cloudera, the furnishing of this document does not give you any license to these patents, trademarks copyrights, or other intellectual property.

The information in this document is subject to change without notice. Cloudera shall not be liable for any damages resulting from technical errors or omissions which may be present in this document, or from use of this document.

Cloudera, Inc.
1001 Page Mill Road, Building 2
Palo Alto, CA 94304-1008
info@cloudera.com
US: 1-888-789-1488
Intl: 1-650-843-0595
www.cloudera.com

Release Information

Version: 2.5.31

Date: February 2, 2016

Table of Contents

INTRODUCTION	5
WINDOWS DRIVER	6
CREATING A DATA SOURCE NAME	6
CONFIGURING AUTHENTICATION	8
CONFIGURING SSL	10
CONFIGURING ADVANCED OPTIONS	11
CONFIGURING SERVER-SIDE PROPERTIES	12
CONFIGURING LOGGING OPTIONS	12
CONFIGURING KERBEROS AUTHENTICATION FOR WINDOWS	14
VERIFYING THE VERSION NUMBER	18
LINUX DRIVER	19
LINUX SYSTEM REQUIREMENTS	19
INSTALLING THE DRIVER	19
SETTING THE LD_LIBRARY_PATH ENVIRONMENT VARIABLE	20
VERIFYING THE VERSION NUMBER	21
MAC OS X DRIVER	22
VERIFYING THE VERSION NUMBER	22
AIX DRIVER	23
INSTALLING THE DRIVER ON AIX	23
SETTING THE LD_LIBRARY_PATH ENVIRONMENT VARIABLE	24
VERIFYING THE VERSION NUMBER	24
DEBIAN DRIVER	25
INSTALLING THE DRIVER ON DEBIAN	25
SETTING THE LD_LIBRARY_PATH ENVIRONMENT VARIABLE	26
VERIFYING THE VERSION NUMBER	26
CONFIGURING ODBC CONNECTIONS FOR NON-WINDOWS PLATFORMS	27
CONFIGURATION FILES	27
SAMPLE CONFIGURATION FILES	28
CONFIGURING THE ENVIRONMENT	28
DEFINING DSNs IN ODBC.INI	29
SPECIFYING ODBC DRIVERS IN ODBCINST.INI	30
CONFIGURING DRIVER SETTINGS IN CLOUDERA.IMPALAODBC.INI	31
CONFIGURING AUTHENTICATION	31
CONFIGURING SSL	33
CONFIGURING SERVER-SIDE PROPERTIES	34

CONFIGURING LOGGING OPTIONS	34
AUTHENTICATION OPTIONS	37
USING A CONNECTION STRING	38
DSN CONNECTION STRING EXAMPLE	38
DSN-LESS CONNECTION STRING EXAMPLES	38
FEATURES	41
DATA TYPES	41
CATALOG AND SCHEMA SUPPORT	42
SQL TRANSLATION	42
SERVER-SIDE PROPERTIES	43
ACTIVE DIRECTORY	43
DRIVER CONFIGURATION OPTIONS	44
CONFIGURATION OPTIONS APPEARING IN THE USER INTERFACE	44
CONFIGURATION OPTIONS HAVING ONLY KEY NAMES	54
APPENDIX A ODBC API CONFORMANCE LEVEL	56
CONTACT US	58

Introduction

The Cloudera ODBC Driver for Impala is used for direct SQL and Impala SQL access to Apache Hadoop / Impala distributions, enabling Business Intelligence (BI), analytics, and reporting on Hadoop / Impala-based data. The driver efficiently transforms an application's SQL query into the equivalent form in Impala SQL, which is a subset of SQL-92. If an application is Impala-aware, then the driver is configurable to pass the query through to the database for processing. The driver interrogates Impala to obtain schema information to present to a SQL-based application. Queries, including joins, are translated from SQL to Impala SQL. For more information about the differences between Impala SQL and SQL, see "Features" on page 41.

The Cloudera ODBC Driver for Impala complies with the ODBC 3.80 data standard and adds important functionality such as Unicode and 32- and 64-bit support for high-performance computing environments.

ODBC is one of the most established and widely supported APIs for connecting to and working with databases. At the heart of the technology is the ODBC driver, which connects an application to the database. For more information about ODBC, see <http://www.simba.com/resources/data-access-standards-library>. For complete information about the ODBC specification, see the *ODBC API Reference* at [http://msdn.microsoft.com/en-us/library/windows/desktop/ms714562\(v=vs.85\).aspx](http://msdn.microsoft.com/en-us/library/windows/desktop/ms714562(v=vs.85).aspx).

The *Installation and Configuration Guide* is suitable for users who are looking to access data residing within Impala from their desktop environment. Application developers may also find the information helpful. Refer to your application for details on connecting via ODBC.

Windows Driver

Creating a Data Source Name

Typically, after installing the Cloudera ODBC Driver for Impala, you need to create a Data Source Name (DSN).

Alternatively, for information about DSN-less connections, see "DSN-less Connection String Examples" on page 38.

To create a Data Source Name:

1. Open the ODBC Administrator:
 - If you are using Windows 7 or earlier, click the **Start** button , then click **All Programs**, then click the **Cloudera ODBC Driver for Impala 2.5** program group corresponding to the bitness of the client application accessing data in Hadoop / Impala, and then click **ODBC Administrator**.
 - Or, if you are using Windows 8 or later, on the Start screen, type **ODBC administrator**, and then click the **ODBC Administrator** search result corresponding to the bitness of the client application accessing data in Hadoop / Impala.
2. In the ODBC Data Source Administrator, click the **Drivers** tab, and then scroll down as needed to confirm that the Cloudera ODBC Driver for Impala appears in the alphabetical list of ODBC drivers that are installed on your system.
3. Choose one:
 - To create a DSN that only the user currently logged into Windows can use, click the **User DSN** tab.
 - Or, to create a DSN that all users who log into Windows can use, click the **System DSN** tab.
4. Click **Add**.
5. In the Create New Data Source dialog box, select **Cloudera ODBC Driver for Impala** and then click **Finish**.
6. In the **Data Source Name** field, type a name for your DSN.
7. Optionally, in the **Description** field, type relevant details about the DSN.
8. Choose one:
9. In the **Host** field, type the IP address or host name of the network load balancer (NLB) or one of the Impala nodes if you are deployed without an NLB.
10. In the **Port** field, type the number of the TCP port that the Impala server uses to listen for client connections.

Note:

The default port number used by Impala is 21050.

11. In the **Database** field, type the name of the database schema to use when a schema is not explicitly specified in a query.

Note:

You can still issue queries on other schemas by explicitly specifying the schema in the query. To inspect your databases and determine the appropriate schema to use, type the **show databases** command at the Impala command prompt.

12. In the Authentication area, configure authentication as needed. For more information, see "Configuring Authentication" on page 8

Note:

The default configuration of Impala requires the Cloudera ODBC Driver for Impala to be configured to use the No Authentication mechanism.

13. To configure an SSL connection, click **SSL Options**. For more information, see "Configuring SSL" on page 10.
14. Optionally, if the operations against Impala are to be done on behalf of a user that is different than the authenticated user for the connection, type the name of the user to be delegated in the **Delegation UID** field.
15. To configure advanced driver options, click **Advanced Options**. For more information, see "Configuring Advanced Options" on page 11.
16. To configure server-side properties, click **Advanced Options** and then click **Server Side Properties**. For more information, see "Configuring Server-Side Properties" on page 12.

Important:

When connecting to Impala 0.14 or later, the Temporary Tables feature is always enabled and you do not need to configure it in the driver.

17. To configure logging behavior for the driver, click **Logging Options**. For more information, see "Configuring Logging Options" on page 12.
18. To test the connection, click **Test**. Review the results as needed, and then click **OK**.

Note:

If the connection fails, then confirm that the settings in the Cloudera ODBC Driver for Impala DSN Setup dialog box are correct. Contact your Impala server administrator as needed.

19. To save your settings and close the Cloudera ODBC Driver for Impala DSN Setup dialog box, click **OK**.
20. To close the ODBC Data Source Administrator, click **OK**.

Configuring Authentication

The Impala server supports multiple authentication mechanisms. You must determine the authentication type your server is using and configure your DSN accordingly. The available authentication methods are as follows:

- No Authentication
- Kerberos
- SASL User Name
- User Name and Password

Note:

In addition to authentication, you can configure the driver to connect over the Secure Sockets Layer (SSL). For more information, see "Configuring SSL" on page 10.

Using No Authentication

For this authentication mechanism, you do not need to configure any additional settings.

Note:

The default configuration of Impala requires the Cloudera ODBC Driver for Impala to be configured to use the No Authentication mechanism.

To configure a connection without authentication:

1. To access authentication options, open the ODBC Data Source Administrator where you created the DSN, then select the DSN, and then click **Configure**.
2. In the Mechanism list, select **No Authentication**.
3. If the Impala server is configured to use SSL, then click **SSL Options** to configure SSL for the connection. For more information, see Configuring SSL Verification on page 1.
4. To save your settings and close the dialog box, click **OK**

Using Kerberos

Kerberos must be installed and configured before you can use this authentication mechanism. For more information, see "Configuring Kerberos Authentication for Windows" on page 14.

To configure Kerberos authentication:

1. To access authentication options, open the ODBC Data Source Administrator where you created the DSN, then select the DSN, and then click **Configure**.
2. In the **Mechanism** list, select **Kerberos**.
3. Choose one:

- To use the default realm defined in your Kerberos setup, leave the **Realm** field empty.
 - Or, if your Kerberos setup does not define a default realm or if the realm of your Impala server host is not the default, then, in the **Realm** field, type the Kerberos realm of the Impala server.
4. In the **Host FQDN** field, type the fully qualified domain name of the Impala server host.

Note:

To use the Impala server host name as the fully qualified domain name for Kerberos authentication, in the **Host FQDN** field, type `_HOST`.

5. In the **Service Name** field, type the service name of the Impala server.
6. In the **Thrift Transport** list, select the transport protocol to use in the Thrift layer.

Important:

When using this authentication mechanism, the Binary transport protocol is not supported.

7. If the Impala server is configured to use SSL, then click **SSL Options** to configure SSL for the connection. For more information, see [Configuring SSL Verification on page 1](#).
8. Optionally, in the **Transport Buffer Size** field, type the number of bytes to reserve in memory for buffering unencrypted data from the network.

Note:

In most circumstances, the default value of 1000 bytes is optimal.

9. To save your settings and close the dialog box, click **OK**.

Using SASL User Name

This authentication mechanism requires a user name but not a password. The user name labels the session, facilitating database tracking.

To configure SASL User Name authentication:

1. To access authentication options, open the ODBC Data Source Administrator where you created the DSN, then select the DSN, and then click **Configure**.
2. In the **Mechanism** list, select **SASL User Name**
3. In the **User Name** field, type an appropriate user name for accessing the Impala server.
4. Optionally, in the **Transport Buffer Size** field, type the number of bytes to reserve in memory for buffering unencrypted data from the network.

Note:

In most circumstances, the default value of 1000 bytes is optimal.

5. To save your settings and close the dialog box, click **OK**.

Using User Name and Password

This authentication mechanism requires a user name and a password.

Note:

This authentication mechanism should not be used with an Impala configuration that does not have LDAP enabled.

To configure User Name and Password authentication:

1. To access authentication options, open the ODBC Data Source Administrator where you created the DSN, then select the DSN, and then click **Configure**.
2. Choose one:
3. In the **Mechanism** list, select **User Name and Password**
4. In the **User Name** field, type an appropriate user name for accessing the Impala server.
5. In the **Password** field, type the password corresponding to the user name you typed above.
6. To save the password, select the **Save Password (Encrypted)** check box.
7. In the **Thrift Transport** list, select the transport protocol to use in the Thrift layer.
8. If the Impala server is configured to use SSL, then click **SSL Options** to configure SSL for the connection. For more information, see [Configuring SSL Verification](#) on page 1.
9. Optionally, in the **Transport Buffer Size** field, type the number of bytes to reserve in memory for buffering unencrypted data from the network.

Note:

In most circumstances, the default value of 1000 bytes is optimal.

10. Optionally, to use SASL to handle authentication, select the **Use Simple Authentication and Security Layer (SASL)** check box.
11. To save your settings and close the dialog box, click **OK**.

Configuring SSL

If you are connecting to an Impala server that has Secure Sockets Layer (SSL) enabled, then you can configure the driver to connect to an SSL-enabled socket.

To configure SSL:

1. To access SSL options, open the ODBC Data Source Administrator where you created the DSN, then select the DSN, then click **Configure**, and then click **SSL Options**.
2. To enable SSL connections, select the **Enable SSL** check box.
3. To allow self-signed certificates from the server, select the **Allow Self-signed Server Certificate** check box.
4. To allow the common name of a CA-issued SSL certificate to not match the host name of the Impala server, select the **Allow Common Name Host Name Mismatch** check box.

5. Choose one:
 - To configure the driver to load SSL certificates from a specific PEM file, type the path to the file in the **Trusted Certificates** field.
 - Or, to use the trusted CA certificates PEM file that is installed with the driver, leave the **Trusted Certificates** field empty.
6. To save your settings and close the SSL Options dialog box, click **OK**.

Configuring Advanced Options

You can configure advanced options to modify the behavior of the driver.

To configure advanced options:

1. To access advanced options, open the ODBC Data Source Administrator where you created the DSN, then select the DSN, then click **Configure**, and then click **Advanced Options**.
2. To disable translation from ODBC SQL to Impala SQL, select the **Use Native Query** check box.

Note:

By default, the driver applies transformations to the queries emitted by an application to convert the queries into an equivalent form in Impala SQL. If the application is Impala-aware and already emits Impala SQL, then turning off the translation avoids the additional overhead of query transformation.

3. To enable the driver to successfully run queries that contain transaction statements, select the **Enable Simulated Transactions** check box.

Note:

The transaction statements are not executed, because ODBC does not support them. Enabling this option allows the driver to run the query without returning error messages.

4. To handle Kerberos authentication using the SSPI plugin instead of MIT Kerberos by default, select one or both of the check boxes under the **Use Only SSPI Plugin** option:
 - To configure the current DSN to use the SSPI plugin by default, select **Enable for this DSN**
 - To configure all DSN-less connections to use the SSPI plugin by default, select **Enable for DSN-less connections**
 - To configure all connections that use the Cloudera ODBC Driver for Impala to use the SSPI plugin by default, select both check boxes.
5. In the **Rows Fetched Per Block** field, type the number of rows to be fetched per block.
6. In the **Socket Timeout Field**, type the number of seconds after which Impala closes the connection with the client application if the connection is idle.

Note:

Setting the Socket timeout value to 0 disables the timeout feature.

7. In the **String Column Length** field, type the maximum data length for STRING columns.
8. To save your settings and close the Advanced Options dialog box, click **OK**.

Configuring Server-Side Properties

When connecting to a server that is running Impala 2.0 or later, you can use the driver to apply configuration properties to the server.

Important:

This feature is not supported for earlier versions of Impala, where the SET statement can only be executed from within the Impala shell.

To configure server-side properties:

1. To configure server-side properties, open the ODBC Data Source Administrator where you created the DSN, then select the DSN, then click **Configure**, then click **Advanced Options**, and then click **Server Side Properties**.
2. To create a server-side property, click **Add**, then type appropriate values in the **Key** and **Value** fields, and then click **OK**. For example, to set the value of the MEM_LIMIT query option to 1 GB, type **MEM_LIMIT** in the **Key** field and then type **1000000000** in the **Value** field.
3. To edit a server-side property, select the property from the list, then click **Edit**, then update the **Key** and **Value** fields as needed, and then click **OK**.
4. To delete a server-side property, select the property from the list, and then click **Remove**. In the confirmation dialog box, click **Yes**.
5. To configure the driver to convert server-side property key names to all lower-case characters, select the **Convert Key Name to Lower Case** check box.
6. To save your settings and close the Server Side Properties dialog box, click **OK**.

Configuring Logging Options

To help troubleshoot issues, you can enable logging. In addition to functionality provided in the Cloudera ODBC Driver for Impala, the ODBC Data Source Administrator provides tracing functionality.

Important:

Only enable logging or tracing long enough to capture an issue. Logging or tracing decreases performance and can consume a large quantity of disk space.

The driver allows you to set the amount of detail included in log files. Table 1 lists the logging levels provided by the Cloudera ODBC Driver for Impala, in order from least verbose to most verbose.

Table 1. Cludera ODBC Driver for Impala Logging Levels

Logging Level	Description
OFF	Disables all logging.
FATAL	Logs very severe error events that will lead the driver to abort.
ERROR	Logs error events that might still allow the driver to continue running.
WARNING	Logs potentially harmful situations.
INFO	Logs general information that describes the progress of the driver.
DEBUG	Logs detailed information that is useful for debugging the driver.
TRACE	Logs more detailed information than the DEBUG level.

To enable driver logging:

1. To access logging options, open the ODBC Data Source Administrator where you created the DSN, then select the DSN, then click **Configure**, and then click **Logging Options**.
2. From the **Log Level** drop-down list, select the desired level of information to include in log files.
3. In the **Log Path** field, specify the full path to the folder where you want to save log files.
4. If requested by Technical Support, type the name of the component for which to log messages in the **Log Namespace** field. Otherwise, do not type a value in the field.
5. In the **Max Number Files** field, type the maximum number of log files to keep.

Note:

After the maximum number of log files is reached, each time an additional file is created, the driver deletes the oldest log file.

6. In the **Max File Size** field, type the maximum size of each log file in megabytes (MB).

Note:

After the maximum file size is reached, the driver creates a new file and continues logging.

7. Click **OK**.
8. Restart your ODBC application to ensure that the new settings take effect.

The Cludera ODBC Driver for Impala produces a log file named `ImpalaODBC_driver.log` at the location that you specify in the Log Path field.

To disable driver logging:

1. Open the ODBC Data Source Administrator where you created the DSN, then select the DSN, then click **Configure**, and then click **Logging Options**.
2. From the **Log Level** drop-down list, select **LOG_OFF**.
3. Click **OK**.

To start tracing using the ODBC Data Source Administrator:

1. In the ODBC Data Source Administrator, click the **Tracing** tab.
2. In the **Log File Path** area, click **Browse**. In the Select ODBC Log File dialog box, browse to the location where you want to save the log file, then type a descriptive file name in the **File name** field, and then click **Save**.
3. On the Tracing tab, click **Start Tracing Now**.

To stop ODBC Data Source Administrator tracing:

- On the Tracing tab in the ODBC Data Source Administrator, click **Stop Tracing Now**.

For more information about tracing using the ODBC Data Source Administrator, see the article *How to Generate an ODBC Trace with ODBC Data Source Administrator* at <http://support.microsoft.com/kb/274551>.

Configuring Kerberos Authentication for Windows

Active Directory

The Cloudera ODBC Driver for Impala supports Active Directory Kerberos on Windows. There are two prerequisites for using Active Directory Kerberos on Windows:

- MIT Kerberos is not installed on the client Windows machine.
- The MIT Kerberos Hadoop realm has been configured to trust the Active Directory realm, according to Cloudera's documentation, so that users in the Active Directory realm can access services in the MIT Kerberos Hadoop realm.

MIT Kerberos

Downloading and Installing MIT Kerberos for Windows 4.0.1

For information about Kerberos and download links for the installer, see the MIT Kerberos website at <http://web.mit.edu/kerberos/>.

To download and install MIT Kerberos for Windows 4.0.1:

1. Download the appropriate Kerberos installer:
 - For a 64-bit computer, use the following download link from the MIT Kerberos website: <http://web.mit.edu/kerberos/dist/kfw/4.0/kfw-4.0.1-amd64.msi>.
 - For a 32-bit computer, use the following download link from the MIT Kerberos website: <http://web.mit.edu/kerberos/dist/kfw/4.0/kfw-4.0.1-i386.msi>.

Note:

The 64-bit installer includes both 32-bit and 64-bit libraries. The 32-bit installer includes 32-bit libraries only.

2. To run the installer, double-click the `.msi` file that you downloaded above.
3. Follow the instructions in the installer to complete the installation process.
4. When the installation completes, click **Finish**.

Setting Up the Kerberos Configuration File

Settings for Kerberos are specified through a configuration file. You can set up the configuration file as an `.INI` file in the default location, which is the `C:\ProgramData\MIT\Kerberos5` directory, or as a `.CONF` file in a custom location.

Normally, the `C:\ProgramData\MIT\Kerberos5` directory is hidden. For information about viewing and using this hidden directory, refer to Microsoft Windows documentation.

Note:

For more information on configuring Kerberos, refer to the MIT Kerberos documentation.

To set up the Kerberos configuration file in the default location:

1. Obtain a `krb5.conf` configuration file. You can obtain this file from your Kerberos administrator, or from the `/etc/krb5.conf` folder on the computer that is hosting the Impala server.
2. Rename the configuration file from `krb5.conf` to `krb5.ini`.
3. Copy the `krb5.ini` file to the `C:\ProgramData\MIT\Kerberos5` directory and overwrite the empty sample file.

To set up the Kerberos configuration file in a custom location:

1. Obtain a `krb5.conf` configuration file. You can obtain this file from your Kerberos administrator, or from the `/etc/krb5.conf` folder on the computer that is hosting the Impala server.
2. Place the `krb5.conf` file in an accessible directory and make note of the full path name.
3. Open your computer Properties window:
 - If you are using Windows 7 or earlier, click the **Start** button , then right-click **Computer**, and then click **Properties**.
 - Or, if you are using Windows 8 or later, right-click **This PC** on the Start screen, and then click **Properties**.
4. Click **Advanced System Settings**.
5. In the System Properties dialog box, click the **Advanced** tab and then click **Environment Variables**.
6. In the Environment Variables dialog box, under the System variables list, click **New**.

7. In the New System Variable dialog box, in the Variable Name field, type **KRB5_CONFIG**.
8. In the **Variable Value** field, type the full path to the `krb5.conf` file.
9. Click **OK** to save the new variable.
10. Make sure that the variable is listed in the System variables list.
11. Click **OK** to close the Environment Variables dialog box, and then click **OK** to close the System Properties dialog box.

Setting Up the Kerberos Credential Cache File

Kerberos uses a credential cache to store and manage credentials.

To set up the Kerberos credential cache file:

1. Create a directory where you want to save the Kerberos credential cache file. For example, create a directory named `C:\temp`.
2. Open your computer Properties window:
 - If you are using Windows 7 or earlier, click the **Start** button , then right-click **Computer**, and then click **Properties**.
 - Or, if you are using Windows 8 or later, right-click **This PC** on the Start screen, and then click **Properties**.
3. Click **Advanced System Settings**
4. In the System Properties dialog box, click the **Advanced** tab and then click **Environment Variables**.
5. In the Environment Variables dialog box, under the System Variables list, click **New**.
6. In the New System Variable dialog box, in the **Variable Name** field, type **KRB5CCNAME**.
7. In the **Variable Value** field, type the path to the folder you created above, and then append the file name `krb5cache`. For example, if you created the folder `C:\temp`, then type `C:\temp\krb5cache`.

Note:

`krb5cache` is a file (not a directory) that is managed by the Kerberos software, and it should not be created by the user. If you receive a permission error when you first use Kerberos, ensure that the `krb5cache` file does not already exist as a file or a directory.

8. Click **OK** to save the new variable.
9. Make sure that the variable appears in the System Variables list.
10. Click **OK** to close the Environment Variables dialog box, and then click **OK** to close the System Properties dialog box.
11. To ensure that Kerberos uses the new settings, restart your computer.

Obtaining a Ticket for a Kerberos Principal

A principal refers to a user or service that can authenticate to Kerberos. To authenticate to Kerberos, a principal must obtain a ticket by using a password or a keytab file. You can specify a keytab file to use, or use the default keytab file of your Kerberos configuration.

To obtain a ticket for a Kerberos principal using a password:

1. Open **MIT Kerberos Ticket Manager**.
2. In the MIT Kerberos Ticket Manager, click **Get Ticket**.
3. In the Get Ticket dialog box, type your principal name and password, and then click **OK**.

If the authentication succeeds, then your ticket information appears in the MIT Kerberos Ticket Manager.

To obtain a ticket for a Kerberos principal using a keytab file:

1. Open a command prompt:
 - If you are using Windows 7 or earlier, click the **Start** button , then click **All Programs**, then click **Accessories**, and then click **Command Prompt**.
 - If you are using Windows 8 or later, click the arrow button at the bottom of the Start screen, then find the Windows System program group, and then click **Command Prompt**.
2. In the Command Prompt, type a command using the following syntax:

```
kinit -k -t keytab_path principal
```

keytab_path is the full path to the keytab file. For example: C:\mykeytabs\myUser.keytab

principal is the Kerberos user principal to use for authentication. For example: myUser@EXAMPLE.COM

3. If the cache location KRB5CCNAME is not set or used, then use the -c option of the kinit command to specify the location of the credential cache. In the command, the -c argument must appear last. For example:

```
kinit -k -t C:\mykeytabs\myUser.keytab myUser@EXAMPLE.COM -c  
C:\ProgramData\MIT\krbcache
```

Krbcache is the Kerberos cache file, not a directory.

To obtain a ticket for a Kerberos principal using the default keytab file:

Note:

For information about configuring a default keytab file for your Kerberos configuration, refer to the MIT Kerberos documentation.

1. Open a command prompt:
 - If you are using Windows 7 or earlier, click the **Start** button , then click **All Programs**, then click **Accessories**, and then click **Command Prompt**.
 - If you are using Windows 8 or later, click the arrow button at the bottom of the Start screen, then find the Windows System program group, and then click **Command Prompt**.
2. In the Command Prompt, type a command using the following syntax:

```
kinit -k [principal]
```

[principal] is the Kerberos user principal to use for authentication, for example, MyUser@EXAMPLE.COM.

3. If the cache location KRB5CCNAME is not set or used, then use the -c option of the kinit command to specify the location of the credential cache. In the command, the -c argument must appear last. For example:

```
kinit -k -t C:\mykeytabs\myUser.keytab myUser@EXAMPLE.COM -c  
C:\ProgramData\MIT\krbcache
```

Krbcache is the Kerberos cache file, not a directory.

Verifying the Version Number

If you need to verify the version of the Cloudera ODBC Driver for Impala that is installed on your Windows machine, you can find the version number in the ODBC Data Source Administrator.

To verify the version number:

1. Open the ODBC Administrator:
 - If you are using Windows 7 or earlier, click the **Start** button , then click **All Programs**, then click the **Cloudera Impala ODBC Driver 2.5** program group corresponding to the bitness of the client application accessing data in Impala, and then click **ODBC Administrator**
 - Or, if you are using Windows 8 or later, on the Start screen, type **ODBC administrator**, and then click the **ODBC Administrator** search result corresponding to the bitness of the client application accessing data in Impala.
2. Click the **Drivers** tab and then find the Cloudera ODBC Driver for Impala in the list of ODBC drivers that are installed on your system. The version number is displayed in the **Version** column.

Linux Driver

Linux System Requirements

You install the Cloudera ODBC Driver for Impala on client machines that access data stored in a Hadoop cluster with the Impala service installed and running. Each machine that you install the driver on must meet the following minimum system requirements:

- One of the following distributions:
 - Red Hat® Enterprise Linux® (RHEL) 5 or 6
 - CentOS 5 or 6
 - SUSE Linux Enterprise Server (SLES) 11 or 12
- 50 MB of available disk space
- One of the following ODBC driver managers installed:
 - iODBC 3.52.7 or later
 - unixODBC 2.3.0 or later

The driver supports Cloudera Impala versions 1.0.1 through 2.2.

Installing the Driver

There are two versions of the driver for Linux:

- **ClouderaImpalaODBC-32bit-[Version]-[Release].[LinuxDistro].i686.rpm** for the 32-bit driver
- **ClouderaImpalaODBC-[Version]-[Release].[LinuxDistro].x86_64.rpm** for the 64-bit driver

[Version] is the version number of the driver, and *[Release]* is the release number for this version of the driver.

The bitness of the driver that you select should match the bitness of the client application accessing your Hadoop / Impala-based data. For example, if the client application is 64-bit, then you should install the 64-bit driver. Note that 64-bit editions of Linux support both 32- and 64-bit applications. Verify the bitness of your intended application and install the appropriate version of the driver.

Important:

Make sure that you install the driver using the RPM corresponding to your Linux distribution.

The Cloudera ODBC Driver for Impala driver files are installed in the following directories:

- **/opt/cloudera/impalaodbc** contains release notes, the *Cloudera ODBC Driver for Impala Installation and Configuration Guide* in PDF format, and a `Readme.txt` file that provides plain text installation and configuration instructions.
- **/opt/cloudera/impalaodbc/ErrorMessage**s contains error message files required by the driver.

- **/opt/cloudera/impalaodbc/Setup** contains sample configuration files named `odbc.ini` and `odbcinst.ini`.
- **/opt/cloudera/impalaodbc/lib/32** contains the 32-bit shared libraries and the `cloudera-impalaodbc.ini` configuration file.
- **/opt/cloudera/impalaodbc/lib/64** contains the 64-bit shared libraries and the `cloudera-impalaodbc.ini` configuration file.

To install the Cloudera ODBC Driver for Impala:

1. Choose one:

- In Red Hat Enterprise Linux or CentOS, log in as the root user, then navigate to the folder containing the driver RPM packages to install, and then type the following at the command line, where `[RPMFileName]` is the file name of the RPM package containing the version of the driver that you want to install:

```
yum --nogpgcheck localinstall [RPMFileName]
```

- In SUSE Linux Enterprise Server, log in as the root user, then navigate to the folder containing the driver RPM packages to install, and then type the following at the command line, where `[RPMFileName]` is the file name of the RPM package containing the version of the driver that you want to install:

```
zypper install [RPMFileName]
```

The Cloudera ODBC Driver for Impala depends on the following resources:

- `cyrus-sasl-2.1.22-7` or above
- `cyrus-sasl-gssapi-2.1.22-7` or above
- `cyrus-sasl-plain-2.1.22-7` or above

If the package manager in your Linux distribution cannot resolve the dependencies automatically when installing the driver, then download and manually install the packages required by the version of the driver that you want to install.

Setting the LD_LIBRARY_PATH Environment Variable

The `LD_LIBRARY_PATH` environment variable must include the paths to the installed ODBC driver manager libraries.

For example, if ODBC driver manager libraries are installed in `/usr/local/lib`, then set `LD_LIBRARY_PATH` as follows:

```
export LD_LIBRARY_PATH=$LD_LIBRARY_PATH:/usr/local/lib
```

For information about how to set environment variables permanently, refer to your Linux shell documentation.

For information about creating ODBC connections using the Cloudera ODBC Driver for Impala, see "Configuring ODBC Connections for Non-Windows Platforms" on page 27.

Verifying the Version Number

If you need to verify the version of the Cloudera ODBC Driver for Impala that is installed on your Linux machine, you can query the version number through the command-line interface if the driver was installed using an RPM file.

To verify the version number:

- Depending on your package manager, at the command prompt, run one of the following commands:

```
yum list | grep ClouderaImpalaODBC
```

```
rpm -qa | grep ClouderaImpalaODBC
```

The command returns information about the Cloudera ODBC Driver for Impala that is installed on your machine, including the version number.

Mac OS X Driver

Verifying the Version Number

If you need to verify the version of the Cloudera ODBC Driver for Impala that is installed on your Mac OS X machine, you can query the version number through the Terminal.

To verify the version number:

- At the Terminal, run the following command:

```
pkgutil --info com.cloudera.impalaodbc
```

The command returns information about the Cloudera ODBC Driver for Impala that is installed on your machine, including the version number.

AIX Driver

Installing the Driver on AIX

There are two versions of the driver for AIX:

- **ClouderaImpalaODBC-32bit-[Version]-[Release].ppc.rpm** for the 32-bit driver
- **ClouderaImpalaODBC-[Version]-[Release].ppc.rpm** for the 64-bit driver

[Version] is the version number of the driver, and *[Release]* is the release number for this version of the driver.

The bitness of the driver that you select should match the bitness of the client application accessing your Hadoop / Impala-based data. For example, if the client application is 64-bit, then you should install the 64-bit driver. Note that 64-bit editions of AIX support both 32- and 64-bit applications. Verify the bitness of your intended application and install the appropriate version of the driver.

You install the Cloudera ODBC Driver for Impala on client machines that access data stored in a Hadoop cluster with the Impala service installed and running. Each machine that you install the driver on must meet the following minimum system requirements:

- IBM AIX 5.3, 6.1, or 7.1 (32- and 64-bit editions are supported)
- 150 MB of available disk space
- One of the following ODBC driver managers installed:
 - iODBC 3.52.7 or later
 - unixODBC 2.3.0 or later

The driver supports Cloudera Impala versions 1.0.1 through 2.2.

The Cloudera ODBC Driver for Impala driver files are installed in the following directories:

- **/opt/cloudera/impalaodbc** contains release notes, the *Cloudera ODBC Driver for Impala Installation and Configuration Guide* in PDF format, and a `Readme.txt` file that provides plain text installation and configuration instructions.
- **/opt/cloudera/impalaodbc/ErrorMessage**s contains error message files required by the driver.
- **/opt/cloudera/impalaodbc/Setup** contains sample configuration files named `odbc.ini` and `odbcinst.ini`
- **/opt/cloudera/impalaodbc/lib/32** contains the 32-bit driver and the `cloudera-impalaodbc.ini` configuration file.
- **/opt/cloudera/impalaodbc/lib/64** contains the 64-bit driver and the `cloudera-impalaodbc.ini` configuration file.

To install the Cloudera ODBC Driver for Impala:

1. Log in as the root user, then navigate to the folder containing the driver RPM packages to install, and then type the following at the command line, where *[RPMFileName]* is the

file name of the RPM package containing the version of the driver that you want to install:

```
rpm --install [RPMFileName]
```

Setting the LD_LIBRARY_PATH Environment Variable

The LD_LIBRARY_PATH environment variable must include the path to the installed ODBC driver manager libraries.

For example, if ODBC driver manager libraries are installed in /usr/local/lib, then set LD_LIBRARY_PATH as follows:

```
export LD_LIBRARY_PATH=$LD_LIBRARY_PATH:/usr/local/lib
```

For information about how to set environment variables permanently, refer to your AIX shell documentation.

For information about creating ODBC connections using the Cloudera ODBC Driver for Impala, see "Configuring ODBC Connections for Non-Windows Platforms" on page 27.

Verifying the Version Number

If you need to verify the version of the Cloudera ODBC Driver for Impala that is installed on your AIX machine, you can query the version number through the command-line interface.

To verify the version number:

- At the command prompt, run the following command:

```
rpm -qa | grep ClouderaImpalaODBC
```

The command returns information about the Cloudera ODBC Driver for Impala that is installed on your machine, including the version number.

Debian Driver

Installing the Driver on Debian

You install the Cloudera ODBC Driver for Impala on client machines that access data stored in a Hadoop cluster with the Impala service installed and running. Each machine that you install the driver on must meet the following minimum system requirements:

- Debian 6 or 7 (Ubuntu 12.04 LTS and Ubuntu 14.04 LTS)
- 150 MB of available disk space
- One of the following ODBC driver managers installed:
 - iODBC 3.52.7 or later
 - unixODBC 2.2.14 or later

The Cloudera ODBC Driver for Impala has been tested using Impala 1.0.1 and Apache Thrift 0.9.0.

There are two versions of the driver for Debian:

- **ClouderaImpalaODBC-32bit-[Version]-[Release]_i386.deb** for the 32-bit driver
- **ClouderaImpalaODBC-[Version]-[Release]_amd64.deb** for the 64-bit driver

[Version] is the version number of the driver, and *[Release]* is the release number for this version of the driver.

The bitness of the driver that you select should match the bitness of the client application accessing your Hadoop / Impala-based data. For example, if the client application is 64-bit, then you should install the 64-bit driver. Note that 64-bit editions of Debian support both 32- and 64-bit applications. Verify the bitness of your intended application and install the appropriate version of the driver.

The Cloudera ODBC Driver for Impala driver files are installed in the following directories:

- **/opt/cloudera/impalaodbc** contains release notes, the *Cloudera ODBC Driver for Impala Installation and Configuration Guide* in PDF format, and a `Readme.txt` file that provides plain text installation and configuration instructions.
- **/opt/cloudera/impalaodbc/ErrorMessage**s contains error message files required by the driver.
- **/opt/cloudera/impalaodbc/Setup** contains sample configuration files named `odbc.ini` and `odbcinst.ini`
- **/opt/cloudera/impalaodbc/lib/32** contains the 32-bit shared libraries and the `cloudera.impalaodbc.ini` configuration file.
- **/opt/cloudera/impalaodbc/lib/64** contains the 64-bit shared libraries and the `cloudera.impalaodbc.ini` configuration file.

To install the Cloudera ODBC Driver for Impala:

1. In Ubuntu, log in as the root user, then navigate to the folder containing the driver Debian packages to install, and double-click **ClouderaImpalaODBC-32bit-Version-Release_i386.deb**

or **ClouderaImpalaODBC-Version-Release_amd64.deb**.

2. Follow the instructions in the installer to complete the installation process.

The Cloudera ODBC Driver for Impala depends on the following resources:

- cyrus-sasl-2.1.22-7 or above
- cyrus-sasl-gssapi-2.1.22-7 or above
- cyrus-sasl-plain-2.1.22-7 or above

If the package manager in your Ubuntu distribution cannot resolve the dependencies automatically when installing the driver, then download and manually install the packages required by the version of the driver that you want to install.

Setting the LD_LIBRARY_PATH Environment Variable

The LD_LIBRARY_PATH environment variable must include the path to the installed ODBC driver manager libraries.

For example, if ODBC driver manager libraries are installed in `/usr/local/lib`, then set LD_LIBRARY_PATH as follows:

```
export LD_LIBRARY_PATH=$LD_LIBRARY_PATH:/usr/local/lib
```

For information about how to set environment variables permanently, refer to your Ubuntu shell documentation.

For information about creating ODBC connections using the Cloudera ODBC Driver for Impala, see "Configuring ODBC Connections for Non-Windows Platforms" on page 27.

Verifying the Version Number

If you need to verify the version of the Cloudera ODBC Driver for Impala that is installed on your Debian machine, you can query the version number through the command-line interface.

To verify the version number:

- At the command prompt, run the following command:

```
dpkg -l | grep ClouderaImpalaODBC
```

The command returns information about the Cloudera ODBC Driver for Impala that is installed on your machine, including the version number.

Configuring ODBC Connections for Non-Windows Platforms

The following sections describe how to configure ODBC connections when using the Cloudera ODBC Driver for Impala with non-Windows platforms:

- "Configuration Files" on page 27
- "Sample Configuration Files" on page 28
- "Configuring the Environment" on page 28
- "Defining DSNs in `odbc.ini`" on page 29
- "Specifying ODBC Drivers in `odbcinst.ini`" on page 30
- "Configuring Driver Settings in `cloudera.impalaodbc.ini`" on page 31
- "Configuring Authentication" on page 31
- "Configuring SSL" on page 33
- "Configuring Server-Side Properties" on page 34
- "Configuring Logging Options" on page 34

Configuration Files

ODBC driver managers use configuration files to define and configure ODBC data sources and drivers. By default, the following configuration files residing in the user's home directory are used:

- `.odbc.ini` is used to define ODBC data sources, and it is required for DSNs.
- `.odbcinst.ini` is used to define ODBC drivers, and it is optional.

Also, by default the Cloudera ODBC Driver for Impala is configured using the `cloudera.impalaodbc.ini` file, which is located in one of the following directories depending on the version of the driver that you are using:

- `/opt/cloudera/impalaodbc/lib/32` for the 32-bit driver on Linux/AIX/Debian
- `/opt/cloudera/impalaodbc/lib/64` for the 64-bit driver on Linux/AIX/Debian
- `/opt/cloudera/impalaodbc/lib/universal` for the driver on Mac OS X

The `cloudera.impalaodbc.ini` file is required.

Note:

The `cloudera.impalaodbc.ini` file in the `/lib` subfolder provides default settings for most configuration options available in the Cloudera ODBC Driver for Impala.

You can set driver configuration options in your `odbc.ini` and `cloudera.impalaodbc.ini` files. Configuration options set in a `cloudera.impalaodbc.ini` file apply to all connections, whereas configuration options set in an `odbc.ini` file are specific to a connection. Configuration options set in `odbc.ini` take precedence over configuration options set in `cloudera.impalaodbc.ini`. For information about the configuration options available for controlling the behavior of DSNs that are using the Cloudera ODBC Driver for Impala, see "Driver Configuration Options" on page 44.

Sample Configuration Files

The driver installation contains the following sample configuration files in the Setup directory:

- **odbc.ini**
- **odbcinst.ini**

These sample configuration files provide preset values for settings related to the Cloudera ODBC Driver for Impala.

The names of the sample configuration files do not begin with a period (.) so that they appear in directory listings by default. A file name beginning with a period (.) is hidden. For `odbc.ini` and `odbcinst.ini`, if the default location is used, then the file names must begin with a period (.).

If the configuration files do not exist in the home directory, then you can copy the sample configuration files to the home directory, and then rename the files. If the configuration files already exist in the home directory, then use the sample configuration files as a guide to modify the existing configuration files.

Configuring the Environment

Optionally, you can use three environment variables, `ODBCINI`, `ODBCSYSINI`, and `CLOUDERAIMPALAINI`, to specify different locations for the `odbc.ini`, `odbcinst.ini`, and `cloudera.impalaodbc.ini` configuration files by doing the following:

- Set `ODBCINI` to point to your `odbc.ini` file.
- Set `ODBCSYSINI` to point to the directory containing the `odbcinst.ini` file.
- Set `CLOUDERAIMPALAINI` to point to your `cloudera.impalaodbc.ini` file.

For example, if your `odbc.ini` and `cloudera.impalaodbc.ini` files are located in `/etc` and your `odbcinst.ini` file is located in `/usr/local/odbc`, then set the environment variables as follows:

```
export ODBCINI=/etc/odbc.ini
export ODBCSYSINI=/usr/local/odbc
export CLOUDERAIMPALAINI=/etc/cloudera.impalaodbc.ini
```

The following search order is used to locate the `cloudera.impalaodbc.ini` file:

1. If the `CLOUDERAIMPALAINI` environment variable is defined, then the driver searches for the file specified by the environment variable.

Important:

`CLOUDERAIMPALAINI` must specify the full path, including the file name.

2. The directory containing the driver's binary is searched for a file named `cloudera.impalaodbc.ini` (not beginning with a period).
3. The current working directory of the application is searched for a file named `cloudera.impalaodbc.ini` (not beginning with a period).

4. The directory `~/` (that is, `$HOME`) is searched for a hidden file named `.cloudera-impalaodbc.ini`.
5. The directory `/etc` is searched for a file named `cloudera.impalaodbc.ini` (not beginning with a period).

Defining DSNs in `odbc.ini`

ODBC Data Source Names (DSNs) are defined in the `odbc.ini` configuration file. This file is divided into several sections:

- `[ODBC]` is optional. This section is used to control global ODBC configuration, such as ODBC tracing.
- `[ODBC Data Sources]` is required. This section lists the DSNs and associates them with a driver.
- A section having the same name as the data source specified in the `[ODBC Data Sources]` section is required to configure the data source.

The following is an example of an `odbc.ini` configuration file for Linux/AIX/Debian:

```
[ODBC Data Sources]
Sample Cloudera Impala ODBC DSN 32=Cloudera Impala ODBC Driver
32-bit
[Sample Cloudera Impala DSN 32]
Driver=/opt/cloudera/impalaodbc/lib/32/libclouderaimpalaodbc32.
so
HOST=[MyImpalaServer]
PORT=21050
```

`[MyImpalaServer]` is the IP address or host name of the Impala server.

The following is an example of an `odbc.ini` configuration file for Mac OS X:

```
[ODBC Data Sources]
Sample Cloudera Impala DSN=Cloudera Impala ODBC Driver
[Sample Cloudera Impala DSN]
Driver=/opt/cloudera/impalaodbc/lib/universal/libclouderaimpala
odbc.dylib
HOST=[MyImpalaServer]
PORT=21050
```

`[MyImpalaServer]` is the IP address or host name of the Impala server.

To create a Data Source Name:

1. In a text editor, open the `odbc.ini` configuration file.
2. In the `[ODBC Data Sources]` section, add a new entry by typing the Data Source Name (DSN), then an equal sign (=), and then the driver name.

3. Add a new section to the file, with a section name that matches the DSN you specified above, and then add configuration options to the section. Specify the configuration options as key-value pairs.

Note:

The default configuration of Impala requires the Cloudera ODBC Driver for Impala to be configured to use the No Authentication mechanism.

4. Save the `odbc.ini` configuration file.

For information about the configuration options available for controlling the behavior of DSNs that are using the Cloudera ODBC Driver for Impala, see "Driver Configuration Options" on page 44.

Specifying ODBC Drivers in `odbcinst.ini`

ODBC drivers are defined in the `odbcinst.ini` configuration file. This configuration file is optional because drivers can be specified directly in the `odbc.ini` configuration file, as described in "Defining DSNs in `odbc.ini`" on page 29.

The `odbcinst.ini` file is divided into the following sections:

- `[ODBC Drivers]` lists the names of all the installed ODBC drivers.
- For each driver, a section having the same name as the driver name specified in the `[ODBC Drivers]` section lists the driver attributes and values.

The following is an example of an `odbcinst.ini` configuration file for Linux/AIX/Debian:

```
[ODBC Drivers]
Cloudera Impala ODBC Driver 32-bit=Installed
Cloudera Impala ODBC Driver 64-bit=Installed
[Cloudera Impala ODBC Driver 32-bit]
Description=Cloudera Impala ODBC Driver (32-bit)
Driver=/opt/cloudera/impalaodbc/lib/32/libclouderaimpalaodbc32.so
[Cloudera Impala ODBC Driver 64-bit]
Description=Cloudera Impala ODBC Driver (64-bit)
Driver=/opt/cloudera/impalaodbc/lib/64/libclouderaimpalaodbc64.so
```

The following is an example of an `odbcinst.ini` configuration file for Mac OS X:

```
[ODBC Drivers]
Cloudera Impala ODBC Driver=Installed
[Cloudera Impala ODBC Driver]
Description=Cloudera Impala ODBC Driver
```

```
Driver=/opt/cloudera/impalaodbc/lib/universal/libclouderaimpalaodbc.dylib
```

To define a driver:

1. In a text editor, open the `odbcinst.ini` configuration file.
2. In the [ODBC Drivers] section, add a new entry by typing the driver name and then typing `=Installed`.

Note:

Give the driver a symbolic name that you want to use to refer to the driver in connection strings or DSNs.

3. Add a new section to the file with a name that matches the driver name you typed above, and then add configuration options to the section based on the sample `odbcinst.ini` file provided in the Setup directory. Specify the configuration options as key-value pairs.
4. Save the `odbcinst.ini` configuration file.

Configuring Driver Settings in `cloudera.impalaodbc.ini`

The `cloudera.impalaodbc.ini` file contains configuration settings for the Cloudera ODBC Driver for Impala. Settings that you define in this file apply to all connections that use the driver.

You do not need to modify the settings in the `cloudera.impalaodbc.ini` file to use the driver and connect to your data source.

However, to help troubleshoot issues, you can configure the `cloudera.impalaodbc.ini` file to enable logging in the driver. For information about configuring logging, see "Configuring Logging Options" on page 34.

Configuring Authentication

The Impala server supports multiple authentication mechanisms. You must determine the authentication type your server is using and configure your DSN accordingly. The available authentication methods are as follows:

- No Authentication
- Kerberos
- SASL User Name
- User Name and Password

Note:

In addition to authentication, you can configure the driver to connect over the Secure Sockets Layer (SSL). For more information, see "Configuring SSL" on page 33.

Using No Authentication

For this authentication mechanism, you do not need to configure any additional settings.

Note:

The default configuration of Impala requires the Cloudera ODBC Driver for Impala to be configured to use the No Authentication mechanism.

To configure a connection without authentication:

- Set the AuthMech connection attribute to 0

Kerberos

Kerberos must be installed and configured before you can use this authentication mechanism. For more information, refer to the MIT Kerberos documentation.

To configure Kerberos authentication:

1. Set the AuthMech connection attribute to 1.
2. To use the default realm defined in your Kerberos setup, do not set the KrbRealm attribute.

If your Kerberos setup does not define a default realm or if the realm of your Impala server is not the default, then set the appropriate realm using the KrbRealm attribute.

3. Set the KrbFQDN attribute to the fully qualified domain name of the Impala server host.

Note:

To use the Impala server host name as the fully qualified domain name for Kerberos authentication, set KrbFQDN to **_HOST**

4. Set the KrbServiceName attribute to the service name of the Impala server.
5. Optionally, set the TSaslTransportBufSize attribute to the number of bytes to reserve in memory for buffering unencrypted data from the network.

Note:

In most circumstances, the default value of 1000 bytes is optimal.

Using SASL User Name

This authentication mechanism requires a user name but does not require a password. The user name labels the session, facilitating database tracking.

To configure SASL User Name authentication:

1. Set the AuthMech connection attribute to 2.
2. Set the UID attribute to an appropriate user name for accessing the Impala server.
3. Optionally, set the TSaslTransportBufSize attribute to the number of bytes to reserve in memory for buffering unencrypted data from the network.

Note:

In most circumstances, the default value of 1000 bytes is optimal.

Using User Name and Password

This authentication mechanism requires a user name and a password.

Note:

This authentication mechanism should not be used with an Impala configuration that does not have LDAP enabled.

To configure User Name and Password authentication:

1. Set the AuthMech connection attribute to 3.
2. Set the UID attribute to an appropriate user name for accessing the Impala server.
3. Set the PWD attribute to the password corresponding to the user name you provided above.
4. Optionally, set the TSaslTransportBufSize attribute to the number of bytes to reserve in memory for buffering unencrypted data from the network.

Note:

In most circumstances, the default value of 1000 bytes is optimal.

5. Optionally, to use SASL to handle authentication, set the UseSASL attribute to 1.

Configuring SSL

If you are connecting to an Impala server that has Secure Sockets Layer (SSL) enabled, then you can configure the driver to connect to an SSL-enabled socket.

To configure SSL:

1. Open the .odbc.ini configuration file in a text editor.
2. To enable SSL connections, set the SSL connection attribute to 1
3. To allow self-signed certificates from the server, set the AllowSelfSignedServerCert attribute to 1
4. To allow the common name of a CA-issued SSL certificate to not match the host name of the Impala server, set the CAIssuedCertNamesMismatch attribute to 1
5. Choose one:
 - To configure the driver to load SSL certificates from a specific PEM file, set the TrustedCerts attribute to the path of the file.
 - Or, to use the trusted CA certificates PEM file that is installed with the driver, do not specify a value for the TrustedCerts attribute.
6. Save the .odbc.ini configuration file.

Configuring Server-Side Properties

When connecting to a server that is running Impala 2.0 or later, you can use the driver to apply configuration properties to the Impala server. You can set these server-side properties in a DSN (in the `odbc.ini` file) or in a connection string.

Important:

Be aware of the following:

- This feature is not supported for earlier versions of Impala, where the SET statement can only be executed from within the Impala shell.
- If server-side properties are set in both the `odbc.ini` file and the connection string, the ones set in the connection string take precedence.

To configure server-side properties:

1. To set a server-side property, use the syntax `SSP_[SSPKey]=[SSPValue]`, where `[SSPKey]` is the name of the server-side property and `[SSPValue]` is the value to specify for that property. For example, to set the `MEM_LIMIT` query option to 1 GB and the `REQUEST_POOL` query option to `myPool`, type the following in the `odbc.ini` file:

```
SSP_MEM_LIMIT=1000000000
```

```
SSP_REQUEST_POOL=myPool
```

Or, to set those properties in a connection string, type the following:

```
SSP_MEM_LIMIT={1000000000};SSP_REQUEST_POOL={myPool}
```

Note:

When setting a server-side property in a connection string, it is recommended that you enclose the value in braces (`{ }`) to ensure that special characters can be properly escaped.

2. To disable the driver's default behavior of converting server-side property key names to all lower-case characters, set the `LCaseSspKeyName` property to 0.
3. To save your settings and close the Server Side Properties dialog box, click **OK**.

Configuring Logging Options

To help troubleshoot issues, you can enable logging in the driver.

Important:

Only enable logging long enough to capture an issue. Logging decreases performance and can consume a large quantity of disk space.

Use the `LogLevel` key to set the amount of detail included in log files. Table 2 lists the logging levels provided by the Cloudera ODBC Driver for Impala, in order from least verbose to most verbose.

Table 2. Cludera ODBC Driver for Impala Logging Levels

LogLevel Value	Description
0	Disables all logging.
1	Logs very severe error events that will lead the driver to abort.
2	Logs error events that might still allow the driver to continue running.
3	Logs potentially harmful situations.
4	Logs general information that describes the progress of the driver.
5	Logs detailed information that is useful for debugging the driver.
6	Logs more detailed information than LogLevel 5

To enable logging:

1. Open the `cloudera.impalaodbc.ini` configuration file in a text editor.
2. Set the `LogLevel` key to the desired level of information to include in log files. For example:
`LogLevel=2`
3. Set the `LogPath` key to the full path to the folder where you want to save log files. For example:
`LogPath=/localhome/employee/Documents`
4. Set the `LogFileCount` key to the maximum number of log files to keep.

Note:

After the maximum number of log files is reached, each time an additional file is created, the driver deletes the oldest log file.

5. Set the `LogFileSize` key to the maximum size of each log file in megabytes (MB).

Note:

After the maximum file size is reached, the driver creates a new file and continues logging.

6. Save the `cloudera.impalaodbc.ini` configuration file.
7. Restart your ODBC application to ensure that the new settings take effect.

The Cludera ODBC Driver for Impala produces a log file named `ImpalaODBC_driver.log` at the location you specify using the `LogPath` key.

To disable logging:

1. Open the `cloudera.impalaodbc.ini` configuration file in a text editor.
2. Set the `LogLevel` key to 0.
3. Save the `cloudera.impalaodbc.ini` configuration file.

Authentication Options

Impala supports multiple authentication mechanisms. You must determine the authentication type that your server is using. The authentication methods available in the Cloudera ODBC Driver for Impala are as follows:

- No Authentication
- Kerberos
- SASL User Name
- User Name and Password

Note:

The default configuration of Impala requires the Cloudera ODBC Driver for Impala to be configured to use the No Authentication mechanism.

In addition to authentication, you can configure the driver to connect over SSL or use SASL to handle authentication.

The Impala server uses SASL (Simple Authentication and Security Layer) to support some of the authentication methods. Kerberos is supported with the SASL GSSAPI mechanism. SASL User Name and User Name and Password (with SASL enabled) are supported with the SASL PLAIN mechanism.

Table 3. Impala Authentication Mechanisms

SASL mechanisms	Non-SASL mechanisms
Kerberos	No Authentication
SASL User Name	User Name and Password (without SASL enabled)
User Name and Password (with SASL enabled)	

Note:

Thrift (the layer for handling remote process communication between the Cloudera ODBC Driver for Impala and the Impala server) has a limitation where it cannot detect a mix of non-SASL and SASL mechanisms being used between the driver and the server. If this happens, the driver will appear to hang during connection establishment.

Using a Connection String

For some applications, you may need to use a connection string to connect to your data source. For detailed information about how to use a connection string in an ODBC application, refer to the documentation for the application that you are using.

The connection strings in the following topics are examples showing the minimum set of connection attributes that you must specify to successfully connect to the data source. Depending on the configuration of the data source and the type of connection you are working with, you may need to specify additional connection attributes. For detailed information about all the attributes that you can use in the connection string, see "Driver Configuration Options" on page 44.

- "DSN Connection String Example" on page 38
- "DSN-less Connection String Examples" on page 38

DSN Connection String Example

The following is an example of a connection string for a connection that uses a DSN:

```
DSN=[DataSourceName];
```

[DataSourceName] is the DSN that you are using for the connection.

You can set additional configuration options by appending key-value pairs to the connection string. Configuration options that are passed in using a connection string take precedence over configuration options that are set in the DSN.

For information about creating a DSN on a Windows computer, see "Creating a Data Source Name" on page 6. For information about creating a DSN on a non-Windows computer, see "Defining DSNs in `odbc.ini`" on page 29.

DSN-less Connection String Examples

Some applications provide support for connecting to a data source using a driver without a DSN. To connect to a data source without using a DSN, use a connection string instead.

The placeholders in the examples are defined as follows, in alphabetical order:

- *DomainName* is the fully qualified domain name of the Impala server host.
- *PortNumber* is the number of the TCP port that the Impala server uses to listen for client connections.
- *Realm* is the Kerberos realm of the Impala server host.
- *Server* is the IP address or host name of the Impala server to which you are connecting.
- *ServiceName* is the Kerberos service principal name of the Impala server.
- *YourPassword* is the password corresponding to your user name.
- *YourUserName* is the user name that you use to access the Impala server.

Connecting to an Impala Server Without Authentication

The following is the format of a DSN-less connection string that connects to an Impala server that does not require authentication:

```
Driver=Cloudera Impala ODBC Driver;Host=Server;Port=PortNumber;
```

For example:

```
Driver=Cloudera Impala ODBC Driver;Host=192.168.222.160;
Port=21050;
```

If you are connecting to the server through SSL, then set the SSL property to 1. For example:

```
Driver=Cloudera Impala ODBC Driver;Host=192.168.222.160;
Port=21050;SSL=1;
```

Connecting to an Impala Server that Requires Kerberos Authentication

The following is the format of a DSN-less connection string that connects to an Impala server requiring **Kerberos** authentication:

```
Driver=Cloudera Impala ODBC Driver;
Host=Server;Port=PortNumber;AuthMech=1;KrbRealm=Realm;
KrbFQDN=DomainName;KrbServiceName=ServiceName;
```

For example:

```
Driver=Cloudera Impala ODBC Driver;
Host=192.168.222.160;Port=21050;AuthMech=1;KrbRealm=CLOUDERA;
KrbFQDN=localhost.localdomain;KrbServiceName=impala;
```

If you are connecting to the server through SSL, then set the SSL property to 1. For example:

```
Driver=Cloudera Impala ODBC Driver;
Host=192.168.222.160;Port=21050;AuthMech=1;KrbRealm=CLOUDERA;
KrbFQDN=localhost.localdomain;KrbServiceName=impala;SSL=1;
```

Connecting to an Impala Server that Requires User Name Authentication

The following is the format of a DSN-less connection string that connects to an Impala server requiring User Name authentication. By default, the driver uses **anonymous** as the user name.

```
Driver=Cloudera Impala ODBC Driver;Host=Server;Port=PortNumber;
AuthMech=2;
```

For example:

```
Driver=Cloudera Impala ODBC Driver;Host=192.168.222.160;
Port=21050;AuthMech=2;
```

If you are connecting to the server through SSL, then set the SSL property to 1. For example:

```
Driver=Cloudera Impala ODBC Driver;Host=192.168.222.160;
Port=21050;AuthMech=2;SSL=1;
```

Connecting to an Impala Server that Requires User Name and Password Authentication

The following is the format of a DSN-less connection string that connects to an Impala server requiring **User Name and Password** authentication:

```
Driver=Cloudera Impala ODBC Driver;  
Host=Server;Port=PortNumber;AuthMech=3;UID=YourUserName;  
PWD=YourPassword;
```

For example:

```
Driver=Cloudera Impala ODBC Driver;  
Host=192.168.222.160;Port=21050;AuthMech=3;UID=cloudera;  
PWD=cloudera;
```

If you are connecting to the server through SSL, then set the SSL property to 1. For example:

```
Driver=Cloudera Impala ODBC Driver;  
Host=192.168.222.160;Port=21050;AuthMech=3;UID=cloudera;  
PWD=cloudera;SSL=1;
```

Features

More information is provided on the following features of the Cloudera ODBC Driver for Impala:

- "Data Types" on page 41
- "Catalog and Schema Support" on page 42
- "SQL Translation" on page 42
- "Server-Side Properties" on page 43
- "Active Directory" on page 43

Data Types

The Cloudera ODBC Driver for Impala supports many common data formats, converting between Impala data types and SQL data types.

Table 4 lists the supported data type mappings.

Table 4. Supported Data Types

Impala Type	SQL Type
ARRAY	SQL_VARCHAR
BIGINT	SQL_BIGINT
BINARY	SQL_VARBINARY
BOOLEAN	SQL_BOOLEAN
CHAR <div data-bbox="233 1234 708 1354" style="border: 1px solid black; padding: 5px; margin-top: 10px;"> <p>Note: Only available in CDH 5.2 or later.</p> </div>	SQL_CHAR <div data-bbox="829 1234 1312 1493" style="border: 1px solid black; padding: 5px; margin-top: 10px;"> <p>Note: SQL_WCHAR is returned instead if the Use SQL Unicode Types configuration option (the UseUnicodeSqlCharacterTypes key) is enabled.</p> </div>
DATE	SQL_DATE
DECIMAL <div data-bbox="233 1633 708 1753" style="border: 1px solid black; padding: 5px; margin-top: 10px;"> <p>Note: Only available in CDH 5.2 or later.</p> </div>	SQL_DECIMAL
DOUBLE	SQL_DOUBLE

Impala Type	SQL Type
<p>Note:</p> <p>REAL is an alias for DOUBLE.</p>	
FLOAT	SQL_REAL
INT	SQL_INTEGER
MAP	SQL_VARCHAR
SMALLINT	SQL_SMALLINT
STRUCT	SQL_VARCHAR
TIMESTAMP	SQL_TIMESTAMP
TINYINT	SQL_TINYINT
<p>VARCHAR</p> <p>Note:</p> <p>Only available in CDH 5.2 or later.</p>	<p>SQL_VARCHAR</p> <p>Note:</p> <p>SQL_WVARCHAR is returned instead if the Use SQL Unicode Types configuration option (the UseUnicodeSqlCharacterTypes key) is enabled.</p>

Catalog and Schema Support

The Cloudera ODBC Driver for Impala supports both catalogs and schemas to make it easy for the driver to work with various ODBC applications. Since Impala only organizes tables into schemas/databases, the driver provides a synthetic catalog called “IMPALA” under which all of the schemas/databases are organized. The driver also maps the ODBC schema to the Impala schema/database.

SQL Translation

The Cloudera ODBC Driver for Impala can parse queries locally before sending them to the Impala server. This feature allows the driver to calculate query metadata without executing the query, support query parameters, and support extra SQL features such as ODBC escape sequences and additional scalar functions that are not available in the Impala-shell tool.

Note:

The driver does not support translation for queries that reference a field contained in a nested column (an ARRAY, MAP, or STRUCT column). To retrieve data from a nested column, ensure that the query is written in valid Impala SQL syntax.

Server-Side Properties

The Cloudera ODBC Driver for Impala allows you to set server-side properties via a DSN. Server-side properties specified in a DSN affect only the connection that is established using the DSN.

For more information about setting server-side properties when using the Windows driver, see "Configuring Server-Side Properties" on page 12. For information about setting server-side properties when using the driver on a non-Windows platform, see "Driver Configuration Options" on page 44.

Active Directory

The Cloudera ODBC Driver for Impala supports Active Directory Kerberos on Windows. There are two prerequisites for using Active Directory Kerberos on Windows:

- MIT Kerberos is **not** installed on the client Windows machine.
- The MIT Kerberos Hadoop realm has been configured to trust the Active Directory realm, according to Cloudera's documentation, so that users in the Active Directory realm can access services in the MIT Kerberos Hadoop realm.

Driver Configuration Options

Driver Configuration Options lists the configuration options available in the Cloudera ODBC Driver for Impala alphabetically by field or button label. Options having only key names, that is, not appearing in the user interface of the driver, are listed alphabetically by key name.

When creating or configuring a connection from a Windows computer, the fields and buttons are available in the Cloudera Impala ODBC Driver Configuration tool and the following dialog boxes:

- Cloudera ODBC Driver for Impala DSN Setup
- SSL Options
- Advanced Options
- Server Side Properties

When using a connection string or configuring a connection from a Linux/Mac OS X/AIX/Debian computer, use the key names provided.

Note:

You can pass in configuration options in your connection string, or set them in your `odbc.ini` and `cloudera.impalaodbc.ini` files if you are using a non-Windows version of the driver. Configuration options set in a `cloudera.impalaodbc.ini` file apply to all connections, whereas configuration options passed in in the connection string or set in an `odbc.ini` file are specific to a connection. Configuration options passed in using the connection string take precedence over configuration options set in `odbc.ini`. Configuration options set in `odbc.ini` take precedence over configuration options set in `cloudera.impalaodbc.ini`

Configuration Options Appearing in the User Interface

The following configuration options are accessible via the Windows user interface for the Cloudera ODBC Driver for Impala, or via the key name when using a connection string or configuring a connection from a Linux/Mac OS X/AIX/Debian computer:

- "Allow Common Name Host Name Mismatch" on page 45
- "Allow Self-signed Server Certificate" on page 45
- "Convert Key Name to Lower Case" on page 46
- "Database" on page 46
- "Delegation UID" on page 46
- "Enable Simulated Transactions" on page 46
- "Enable SSL" on page 47
- "Host" on page 47
- "Rows Fetched Per Block" on page 49
- "Save Password (Encrypted)" on page 49
- "Service Name" on page 50
- "Socket Timeout" on page 50
- "String Column Length" on page 50
- "Transport Buffer Size" on page 51
- "Trusted Certificates" on page 51
- "Use Native Query" on page 51
- "Use Only SSPI Plugin" on page 52
- "Use Simple Authentication and Secur-

- "Host FQDN" on page 48
- "Mechanism" on page 48
- "Password" on page 48
- "Port" on page 49
- "Realm" on page 49
- "Security Layer (SASL)" on page 53
- "Use SQL Unicode Types" on page 53
- "User Name" on page 53

Allow Common Name Host Name Mismatch

Key Name	Default Value	Required
CAIssuedCertNamesMismatch	Clear (0)	No

Description

This option specifies whether a CA-issued SSL certificate name must match the host name of the Impala server.

- Enabled (1): The driver allows a CA-issued SSL certificate name to not match the host name of the Impala server.
- Disabled (0): The CA-issued SSL certificate name must match the host name of the Impala server.

Note:

This setting is applicable only when SSL is enabled.

Allow Self-signed Server Certificate

Key Name	Default Value	Required
AllowSelfSignedServerCert	Clear (0)	No

Description

This option specifies whether the driver allows self-signed certificates from the server.

- Enabled (1): The driver authenticates the Impala server even if the server is using a self-signed certificate.
- Disabled (0): The driver does not allow self-signed certificates from the server.

Note:

This setting is applicable only when SSL is enabled.

Convert Key Name to Lower Case

Key Name	Default Value	Required
LCASESSPKeyName	Selected (1)	No

Description

This option specifies whether the driver converts server-side property key names to all lower-case characters.

- Enabled (1): The driver converts server-side property key names to all lower-case characters.
- Disabled (0): The driver does not modify the server-side property key names.

Database

Key Name	Default Value	Required
Schema	default	No

Description

The name of the database schema to use when a schema is not explicitly specified in a query. You can still issue queries on other schemas by explicitly specifying the schema in the query.

Note:

To inspect your databases and determine the appropriate schema to use, at the Impala command prompt, type `show databases`.

Delegation UID

Key Name	Default Value	Required
DelegationUID	None	No

Description

If a value is specified for this setting, the driver delegates all operations against Impala to the specified user, rather than to the authenticated user for the connection.

Enable Simulated Transactions

Key Name	Default Value	Required
EnableSimulatedTransactions	Clear (0)	No

Description

This option specifies whether the driver should simulate transactions, or return an error.

- Enabled (1): The driver simulates transactions, enabling queries that contain transaction statements to be run successfully. The transactions are not executed.
- Disabled (0): The driver returns an error if it attempts to run a query that contains transaction statements.

Note:

ODBC does not support transaction statements, so they cannot be executed.

Enable SSL

Key Name	Default Value	Required
SSL	Clear (0)	No

Description

This option specifies whether the driver communicates with the Impala server through an SSL-enabled socket.

- Enabled (1): The driver communicates with the Impala server through an SSL-enabled socket.
- Disabled (0): The driver does not connect to SSL-enabled sockets.

Note:

SSL is configured independently of authentication. When authentication and SSL are both enabled, the driver performs the specified authentication method over an SSL connection.

Host

Key Name	Default Value	Required
HOST	None	Yes

Description

The IP address or host name of the Impala server.

Host FQDN

Key Name	Default Value	Required
KrbFQDN	None	Yes, if the authentication mechanism is Kerberos.

Description

The fully qualified domain name of the Impala host.

You can set the value of Host FQDN to `_HOST` to use the Impala server host name as the fully qualified domain name for Kerberos authentication.

Mechanism

Key Name	Default Value	Required
AuthMech	No Authentication (0)	No

Description

The authentication mechanism to use.

Select one of the following settings, or set the key to the corresponding number:

- No Authentication (0)
- Kerberos (1)
- SASL User Name (2)
- User Name and Password (3)

Password

Key Name	Default Value	Required
PWD	None	Yes, if the authentication mechanism is User Name And Password.

Description

The password corresponding to the user name that you provided in the User Name field or `UID` key.

Port

Key Name	Default Value	Required
PORT	21050	Yes

Description

The number of the TCP port that the Impala server uses to listen for client connections.

Realm

Key Name	Default Value	Required
KrbRealm	Depends on your Kerberos configuration.	No

Description

The realm of the Impala host.

If your Kerberos configuration already defines the realm of the Impala host as the default realm, then you do not need to configure this option.

Rows Fetched Per Block

Key Name	Default Value	Required
RowsFetchedPerBlock	10000	No

Description

The maximum number of rows that a query returns at a time.

Any positive 32-bit integer is a valid value, but testing has shown that performance gains are marginal beyond the default value of 10000 rows.

Save Password (Encrypted)

Key Name	Default Value	Required
N/A	Clear (0)	No

Description

This option specifies whether the password is saved in the registry.

Driver Configuration Options

- Enabled (1): The password is saved in the registry.
- Disabled (0): The password is not saved in the registry.

This option is available only in the Windows driver. It appears in the Cloudera ODBC Driver for Impala DSN Setup dialog box.

Important:

The password is obscured (not saved in plain text). However, it is still possible for the encrypted password to be copied and used.

Service Name

Key Name	Default Value	Required
		Yes, if the authentication mechanism is Kerberos.

Description

The Kerberos service principal name of the Impala server.

Socket Timeout

Key Name	Default Value	Required
SocketTimeout	0	No

Description

The number of seconds after which Impala closes the connection with the client application if the connection is idle.

When this option is set to 0, the connection does not time out.

String Column Length

Key Name	Default Value	Required
StringColumnLength	32767	No

Description

The maximum number of characters that can be contained in STRING columns.

Transport Buffer Size

Key Name	Default Value	Required
TSaslTransportBufSize	1000	No

Description

The number of bytes to reserve in memory for buffering unencrypted data from the network.

Note:

In most circumstances, the default value of 1000 bytes is optimal.

Trusted Certificates

Key Name	Default Value	Required
TrustedCerts	<p>The cacerts .pem file in the \lib folder or subfolder within the driver's installation directory.</p> <p>The exact file path varies depending on the version of the driver that is installed. For example, the path for the Windows driver is different from the path for the Mac OS X driver.</p>	No

Description

The location of the .pem file containing trusted CA certificates for authenticating the Impala server when using SSL.

If this option is not set, then the driver defaults to using the trusted CA certificates .pem file installed by the driver.

Note:

This setting is applicable only when SSL is enabled.

Use Native Query

Key Name	Default Value	Required
UseNativeQuery	Clear (0)	No

Description

This option specifies whether the driver uses native Impala SQL queries, or converts them into an equivalent form in Impala SQL.

- Enabled (1): The driver does not transform the queries emitted by an application, and executes Impala SQL queries directly.
- Disabled (0): The driver transforms the queries emitted by an application and converts them into an equivalent form in Impala SQL.

When this option is enabled (1), the driver does not transform the queries emitted by an application, and executes Impala SQL queries directly.

When this option is disabled (0), the driver transforms the queries emitted by an application and converts them into an equivalent form in Impala SQL.

Note:

If the application is Impala-aware and already emits Impala SQL, then enable this option to avoid the extra overhead of query transformation.

Use Only SSPI Plugin

Key Name	Default Value	Required
UseOnlySSPI	Clear (0)	No

Description

This option specifies how the driver handles Kerberos authentication: either with the SSPI plugin or with MIT Kerberos.

- Enable For This DSN (1 in the DSN entry in the registry): The driver handles Kerberos authentication in the DSN connection by using the SSPI plugin instead of MIT Kerberos by default.
- Enable For DSN-less Connections (1 in the driver configuration section of the registry): The driver handles Kerberos authentication in DSN-less connections by using the SSPI plugin instead of MIT Kerberos by default.

If you want all connections that use the Cloudera ODBC Driver for Impala to use the SSPI plugin by default, then enable Use Only SSPI Plugin for both DSN and DSN-less connections.

- Disabled (0): The driver uses MIT Kerberos to handle Kerberos authentication, and only uses the SSPI plugin if the gssapi library is not available.

Important:

This option is available only in the Windows driver.

Use Simple Authentication and Security Layer (SASL)

Key Name	Default Value	Required
UseSASL	0 if using No Authentication. 1 if using User Name and Password or Kerberos or SASL User Name authentication.	No

Description

This option specifies whether the driver uses SASL to handle authentication.

- Enabled (1): The driver uses SASL to handle authentication.
- Disabled (0): The driver does not use SASL.

This option is configurable only when you are using the User Name and Password authentication mechanism. If the driver is configured to use the other authentication mechanisms, then it uses the default setting for the Use Simple Authentication and Security Layer (SASL) option.

Use SQL Unicode Types

Key Name	Default Value	Required
UseUnicodeSqlCharacterTypes	Clear (0)	No

Description

This option specifies the SQL types to be returned for string data types.

- Enabled (1): The driver returns SQL_WVARCHAR for STRING and VARCHAR columns, and returns SQL_WCHAR for CHAR columns.
- Disabled (0): The driver returns SQL_VARCHAR for STRING and VARCHAR columns, and returns SQL_CHAR for CHAR columns.

User Name

Key Name	Default Value	Required
UID	For User Name authentication only, the default value is <code>anonymous</code>	Yes, if the authentication mechanism is User Name and Password. No, if the authentication mechanism is SASL User Name.

Description

The user name that you use to access the Impala server.

Configuration Options Having Only Key Names

The following configuration options do not appear in the Windows user interface for the Cloudera ODBC Driver for Impala and are only accessible when using a connection string or configuring a connection from a Linux/Mac OS X/AIX/Debian computer:

- "Driver" on page 54
- "SSP_" on page 54

Driver

Default Value	Required
The default value varies depending on the version of the driver that is installed. For example, the value for the Windows driver is different from the value of the Mac OS X driver.	Yes

Description

The name of the installed driver (Cloudera ODBC Driver for Impala) or the absolute path of the Cloudera ODBC Driver for Impala shared object file.

SSP_

Default Value	Required
None	No

Description

Set a server-side property by using the following syntax, where *[SSPKey]* is the name of the server-side property and *[SSPValue]* is the value for that property:

```
SSP_[SSPKey]=[SSPValue]
```

For example:

```
SSP_MEM_LIMIT=1000000000
SSP_REQUEST_POOL=myPool
```

Or, to set those properties in a connection string, type the following:

```
SSP_MEM_LIMIT={1000000000};SSP_REQUEST_POOL={myPool}
```

After the driver applies the server-side property, the `SSP_` prefix is removed from the DSN entry, leaving an entry of `SSPKey=SSPValue`.

Important:

This property is supported only for connections to Impala 2.0 or later. In earlier versions of Impala, the SET statement can only be executed from within the Impala shell.

Note:

Note the following:

- The `SSP_` prefix must be upper case.
- When setting a server-side property in a connection string, it is recommended that you enclose the value in braces (`{ }`) to ensure that special characters can be properly escaped.

Appendix A ODBC API Conformance Level

Table 5 lists the ODBC interfaces that the Cloudera ODBC Driver for Impala implements and the ODBC compliance level of each interface.

ODBC compliance levels are Core, Level 1, and Level 2. These compliance levels are defined in the ODBC Specification published with the Interface SDK from Microsoft.

Interfaces include both the Unicode and non-Unicode versions. For more information, see <http://msdn.microsoft.com/en-us/library/ms716246%28VS.85%29.aspx>.

Table 5. ODBC API Conformance Level

Conformance Level	INTERFACES		Conformance Level	INTERFACES
Core	SQLAllocHandle		Core	SQLGetStmtAttr
Core	SQLBindCol		Core	SQLGetTypeInfo
Core	SQLBindParameter		Core	SQLNativeSql
Core	SQLCancel		Core	SQLNumParams
Core	SQLCloseCursor		Core	SQLNumResultCols
Core	SQLColAttribute		Core	SQLParamData
Core	SQLColumns		Core	SQLPrepare
Core	SQLConnect		Core	SQLPutData
Core	SQLCopyDesc		Core	SQLRowCount
Core	SQLDescribeCol		Core	SQLSetConnectAttr
Core	SQLDisconnect		Core	SQLSetCursorName
Core	SQLDriverconnect		Core	SQLSetDescField
Core	SQLEndTran		Core	SQLSetDescRec
Core	SQLExecDirect		Core	SQLSetEnvAttr
Core	SQLExecute		Core	SQLSetStmtAttr
Core	SQLFetch		Core	SQLSpecialColumns

Conformance Level	INTERFACES		Conformance Level	INTERFACES
Core	SQLFetchScroll		Core	SQLStatistics
Core	SQLFreeHandle		Core	SQLTables
Core	SQLFreeStmt		Core	SQLBrowseConnect
Core	SQLGetConnectAttr		Core	SQLPrimaryKeys
Core	SQLGetCursorName		Core	SQLGetInfo
Core	SQLGetData		Level 1	SQLProcedureColumns
Core	SQLGetDescField		Level 1	SQLProcedures
Core	SQLGetDescRec		Level 2	SQLColumnPrivileges
Core	SQLGetDiagField		Level 2	SQLDescribeParam
Core	SQLGetDiagRec		Level 2	SQLForeignKeys
Core	SQLGetEnvAttr		Level 2	SQLTablePrivileges
Core	SQLGetFunctions			

Contact Us

If you are having difficulties using the driver, our [Community Forum](#) may have your solution. In addition to providing user to user support, our forums are a great place to share your questions, comments, and feature requests with us.

If you are a Subscription customer you may also use the [Cloudera Support Portal](#) to search the Knowledge Base or file a Case.

Important:

To help us assist you, prior to contacting Cloudera Support please prepare a detailed summary of the client and server environment including operating system version, patch level, and configuration.